

55SVH7E		
PANEL	Screen Size	55"
	Panel Technology	IPS
	Aspect Ratio	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness (Typ.)	700 cd/m ²
	Contrast Ratio	1,200:1
	Viewing Angle (H x V)	178 X 178
	Response Time	8 ms (G to G)
	Surface Treatment	Haze 3%
	Life Time (Typ.)	60,000 Hrs
	Operation Hours	24 Hrs
	Orientation	Landscape & Portrait
CONNECTIVITY	Input	HDMI (2), DP, DVI-D, RGB, Audio, USB 2.0
	Output	DP, Audio
	External Control	RS232C In/out, RJ45 In/out, IR In
MECHANICAL SPECIFICATION	Bezel Color	Black
	Bezel Width	0.44 mm (Even)
	Monitor Dimension (W x H x D)	1,210.51 x 681.22 x 86.5 mm
	Weight (Head)	16.8 kg
	Carton Dimensions (W x H x D)	1,353.0 x 855.0 x 263.0 mm
	Packed Weight	23.6 kg
	Handle	Yes
	VESA™ Standard Mount Interface	600 x 400 mm
KEY FEATURE	Internal Memory 8GB (System 4GB, Available 4GB), Temperature Sensor, Tile Mode (Up to 15x15), Natural Mode @Tile Mode, ISM Method, DPM Select, Smart Energy Saving, Contents Scheduling(USB, Internal Memory), USB Cloning, Easy Brightness Control, Calibration Mode, Content Rotation, OSD Portrait Mode, Sync Mode, PM Mode, Still Image Diagnosis, HDMI-CEC ¹⁾ , Wake on LAN, Fail Over, No Signal Image (Up to 5MB), Embedded Template, Check Screen (via Pixel Sensor), OPS Power Control, Scan Inversion (with Pivot Mode)	
ENVIRONMENT CONDITIONS	Operation Temperature	0°C to 40°C
	Operation Humidity	10% to 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
	Power Consumption Typ.	170 W
	Power Consumption Max.	220 W
CERTIFICATION	Safety	IEC 60950-1 / EN 60950-1 / UL 60950-1
	EMC	FCC Class "A" / CE / KC
	ErP / Energy Star	N/A / Yes (Energy Star 7.0)
MEDIA PLAYER COMPATIBILITY	OPS Type Compatible	Yes (Piggyback)
	External Media Player Attachable	Yes (MP500/MP700)
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign CMS
	Control and Monitoring Software	SuperSign Control / Control+
ACCESSORIES	Basic	Remote Controller, Power Cord, RS232C Cable, LAN Cable, DP Cable, IR Receiver, Guide Bracket, Screws, Manual
	Optional	Wall Mount (Landscape: WM-L640V, Portrait: WM-P640V), OPS Kit (KT-OPSA)

1) Compatibility may differ by equipment.

Conessioni

