

		55LV77A
PANEL	Screen Size	55" (54.64" measured diagonal)
	Panel Technology	IPS
	Aspect Ratio	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	500cd / m2 (LV75A), 700cd / m2 (LV77A)
	Contrast Ratio	1,400:1
	Dynamic CR	500,000:1
	Viewing Angle (H x V)	178 x 178
	Response Time	12ms (G to G)
CONNECTIVITY	Input	
	Digital	DVI-D(1), HDMI(1), Display Port(1) with HDCP for all input
	Analog	RGB(1), Shared Component(1), AV (1)
	Audio	PC Audio In (1)
	External Control	RS232C (1), RJ45 (1), IR Receiver (1)
	USB	USB (1)
	Output	
	Digital	Display Port (1)
	Analog	RGB(1)
	Audio	Audio Out (1)
	External Control	RS232C (1)
	Audio	
	Auto Volume	No
	Balance	No
	Audio Power	No
	Speaker On/off	No
	Clear Voice II	No
	Sound mode	No
PHYSICAL SPECIFICATION	Bezel Width	2.25mm (L/T) / 1.25mm (R/B)
	Monitor Dimension (W x H x D)	1213.4mm x 684.2mm x 88.5mm
	Weight (Head)	23kg
	Carton Dimensions (W x H x D)	1353mm x 850mm x 255mm
	Packed Weight	30kg
	VESA™ Standard Mount Interface	600mm x 400mm
SPECIAL FEATURES	Additional	Smart Energy Saving, Temp Sensor, Up to 1.5x15 Tile Mode, USB Playback
ENVIRONMENTAL CONDITIONS	Operating Temperature	0°C ~ 40°C
	Operating Humidity	10% ~ 80%
POWER	Power Supply	100 -240V~, 50/60Hz
	Power Consumption	
	Typical / Smart Energy Saving	160W(Typ) / 90W(SES)
	DPMS	0.7W
	Power Off	0.7W
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC
	EMC	FCC Class "B" / CE / KCC
	ErP / Energy Star	Yes / Yes (Energy Star 6.0)
MEDIA PLAYER COMPATIBILITY	Slot PC Compatible (optional)	No
	External Media player Attachable	Yes
SOFTWARE COMPATIBILITY	SuperSign Elite-w lite / Elite-c	Yes / Yes
ACCESSORIES	Included	Remote Controller, Power Cable, DP Cable, Manual, IR Receiver, RS-232C Cable, Tiling Guide, Screw
EAN		8806084924230

Conessioni

55LV77A



HDMI™



55"

