

		55VX1D
PANEL	Screen Size	55"
	Panel Technology	IPS
	Aspect Ratio	16:9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	1,500 cd/m ²
	Contrast Ratio	1,300:1
	Dynamic CR	500,000:1
	Viewing Angle (H x V)	178 x 178
	Response Time	8 ms (G to G)
	Surface Treatment	Hard coating (2H), Anti-glare treatment of the front polarizer (Haze 3% Typ.)
CONNECTIVITY	Operation Hours	24 Hours
	Orientation	Landscape & Portrait
	Input	HDMI, DP, DVI-D, RGB, Audio In, USB 3.0
PHYSICAL SPECIFICATION	Output	DP, Audio Out
	External Control	RS232C In/Out, RJ45 In/Out, IR Receiver In
	Bezel Color	-
	Bezel Width (B to B)*	2.25 mm (L/T) / 1.25 mm (R/B)
	Monitor Dimension (W x H x D)	1,213.4 x 684.2 x 92.8 mm
	Weight (Head)	23.5 kg
	Carton Dimensions (W x H x D)	1,353 x 855 x 263 mm
SPECIAL FEATURES	Packed Weight	36.6 kg
	VESA™ Standard Mount Interface	600 x 400 mm
ENVIRONMENT CONDITIONS	Temperature sensor, Tile mode (Up to 15 x 15), Natural mode @Tile mode, ISM method, DPM select, Energy saving, Smart energy saving, File play with USB, Internal memory (8GB, System 4GB + Available 4GB), USB cloning, Contents scheduling, Fail over, Media share	
	Operation Temperature Range	0°C ~ 40°C
POWER	Operation Humidity Range	10% ~ 80%
	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
	Power Typ. / Max. Consumption Smart Energy Saving	250 W / 280 W
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC
	EMC	FCC Class "A" / CE / KCC
	ErP / Energy Star	NA / Yes (Energy Star 7.0)
MEDIA PLAYER	OPS Type Compatible	-
COMPATIBILITY	External Media Player Attachable	Yes (MP500/MP700)
SOFTWARE	Content Management Software	SuperSign Premium
COMPATIBILITY	Control and Monitoring Software	SuperSign Link
ACCESSORIES	Basic	Remote controller, Power cable, DP cable, Manual, IR receiver, RS-232C cable, LAN cable, Guide bracket, Screws
	Optional	Wall mount (Landscape: WM-L640V, Portrait: WM-P640V)
EAN		8806087764260

Connessioni

- ① HDMI IN
- ② DVI-D IN
- ③ DP IN
- ④ DP OUT
- ⑤ USB IN
- ⑥ RGB/COMPONENT/AV IN
- ⑦ AUDIO IN
- ⑧ AUDIO OUT
- ⑨ LAN IN
- ⑩ LAN OUT
- ⑪ IR IN
- ⑫ RS-232C IN
- ⑬ RS-232C OUT



Disegno Tecnico

55"

1,213.4 x 684.2 x 92.8 mm /

23.5 kg

