

		49VL5B
PANEL	Screen Size	49" (48.50" measured diagonally)
	Panel Technology	IPS
	Aspect Ratio	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	450cd/m ²
	Contrast Ratio	1,300 : 1
	Viewing Angle (H x V)	178 x 178
	Response Time	8ms (G to G)
	Surface Treatment	Hard coating (3H), Anti-glare treatment of the front polarizer (Haze 10%)
	Life time	50,000 Hrs
CONNECTIVITY	Orientation	Portrait & Landscape
	Input	HDMI, DVI-D, RGB
	Output	DVI-D
PHYSICAL SPECIFICATION	External Control	RS232C (In/Out), RJ45, IR Receiver, USB
	Bezel Color	Black
	Bezel Width	2.3mm (Left / Top), 1.2mm (Right / Bottom)
	Monitor Dimension (W x H x D)	1,077.7 x 607.8 x 89.7mm
	Weight (Head)	17.8kg
	Carton Dimensions (W x H x D)	1,214 x 778 x 263mm
	Packed Weight	22.8kg
SPECIAL FEATURES	VESA™ Standard Mount Interface	600 x 400mm
		Temperature Sensor, Tile Mode (Up to 15x15), Natural Mode@Tile Mode, Energy Saving, Smart Energy Saving, File Play with USB
ENVIRONMENTAL CONDITIONS	Operation Temperature Range	0°C to 40°C
	Operation Humidity Range	10% to 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-in Power
	Power Consumption Typ.	90W
	Power Consumption Smart Energy Saving	40W
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC
	EMC	FCC Class "A" / CE / KCC
	ErP / Energy Star	NA / Yes (Energy Star 6.0)
MEDIA PLAYER COMPATIBILITY	Slot PC compatible (optional)	No
	External Media player Attachable	Yes
SOFTWARE COMPATIBILITY	SuperSign-W/Lite	Yes
	SuperSign-C	Yes
ACCESSORY	Accessory	Remote Control, Power Cable, DVI Cable, Manual, IR Receiver, RS-232C Cable, Guide Bracket, Screw
	Optional Accessory	Wall Mount (Landscape: WM-L640V, Portrait: WM-P640V)
EAN		8806087545364

Conessioni

- 1 RS-232C IN

2 RS-232C OUT

3 USB

4 HDMI IN


5 DVI IN
- 6 DVI OUT

7 RGB/AV/COMPONENT IN

8 IR IN

9 LAN

49VL5B



Disegno Tecnico

49"
1,077.7 x 607.8 x 89.7mm /
17.8kg

