

		65EJ5E	55EJ5E
PANEL	Screen Size	65"	55"
	Panel Technology	OLED	OLED
	Aspect Ratio	16 : 9	16 : 9
	Native Resolution	3,840 x 2,160 (UHD)	1,920 x 1,080 (FHD)
	Brightness (Typ.)	400/150 cd/m² (Average Picture Level 25%/100%)	400/150 cd/m² (Average Picture Level 25%/100%)
	Viewing Angle (H x V)	178 x 178	178x178
	Response Time	1ms (G to G), 8ms (MPRT)	1ms (G to G), 8ms (MPRT)
	Surface Treatment (Haze)	Hard Coating (2H), Anti-reflection Treatment of the Front Polarizer (Reflectance Typ. 1.2%)	Hard Coating (2H), Anti-reflection Treatment of the Front Polarizer (Reflectance Typ. 1.2%)
	Life Time (Typ.)	30,000 Hrs	30,000 Hrs
	Operation Hours	12 Hrs / 7 Days * Moving Video Only	18 Hrs / 7 Days * Moving Video Only
	Orientation	Landscape & Portrait	Landscape & Portrait
CONNECTIVITY	Input	HDMI, DP, USB 2.0 (2)	HDMI, DP, USB 2.0 (2)
	Output	DP, Audio	DP, Audio
	External Control	RS232C In/out, RJ45 (LAN) In/out, IR In	RS232C In/out, RJ45 (LAN) In/out, IR In
PHYSICAL SPECIFICATION	Bezel Color	Black	Black
	Bezel Width	0.9 mm (Even) * Off-Bezel 8.1 mm (T), 10.7 mm (B), 8.3 mm (L/R) * On-Bezel	0.9 mm (Even) * Off-Bezel 5.3 mm (T/L/R), 11.0 mm (B) * On-Bezel
	Dimension (W x H x D)	(Head) 1,445.1 x 822.6 x 6.0 mm (Signage Box) 782.8 x 35.5 x 239.0 mm	(Head) 1220.3 x 696.8 x 4.9 mm (Signage Box) 782.8 x 238.4 x 34.7 mm
	Weight	13.5 kg (Set)	10 kg (Set)
	Carton Dimensions (W x H x D)	1,590 x 965 x 205 mm	1,350 x 837 x 250 mm
	Packed Weight	23.4 kg	22.9 kg
SPECIAL FEATURES		Internal Memory (64GB), Temperature Sensor, Embedded CMS (USB Auto Playback, Local Contents Scheduling, Group Manager), Fail Over, Content Sync (RS232C, Local Network), OSD Rotation, Tile Mode Setting, Setting Data Cloning, Firmware Update by Network, SNMP, ISM Mode, Control Manager, Crestron Connected ¹⁾ , DPM, PM Mode, Wake on LAN, Power on Delay, HDMI-CEC ²⁾ , SI Server Setting, webRTC	
ENVIRONMENT CONDITIONS	Operation Temperature Range	0°C ~ 40°C	0°C ~ 40°C
	Operation Humidity Range	10% ~ 80%	10% ~ 80%
POWER	Power Supply	100-240V~, 50/60Hz	100-240V~, 50/60Hz
	Power Type	Built-In Power	Built-In Power
	Power Consumption Typ. / Max.	440 W / 478 W * 8 Color Bar Based	309 W / 318 W * 8 Color Bar Based
STANDARD (CERTIFICATION)	Safety	IEC 60950-1 / EN 60950-1 / UL 60950-1	IEC 60950-1 / EN 60950-1 / UL 60950-1
	EMC	FCC Class "A" / CE / KC	FCC Class "A" / CE / KC
	ErP / Energy Star	Yes / No	Yes / No
MEDIA PLAYER COMPATIBILITY	OPS Type Compatible	No	No
	External Media Player Attachable	Yes	Yes
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign CMS	SuperSign CMS
	Control and Monitoring Software	SuperSign Control+ / Control	SuperSign Control+ / Control
ACCESSORIES	Basic	Remote Controller, Power Cord, QSG, IR Receiver, Regulation Book, Phone to RS232C Gender, RS232 Cable (4p-4p), FFC Cables (for Connection Between Panel and Signage Box), DP Cable, LAN Cable, LC (VLC Cable), Wall Fixers, Wall Fixer Install Guide, Install Guide Sheets, Tapes (for Cabling and Dust Proof), Screws	

1) Network Based Control 2) Compatibility may differ by equipment.

Connessioni

65EJ5E / 55EJ5E



- 1 USB 2.0

2 HDMI IN

3 DP IN

4 DP OUT
- 5 USB 2.0

6 LAN IN

7 LAN OUT

8 IR IN

- 9 RS232C IN

10 RS232C OUT

11 AUDIO OUT

