

		65EE5PC
PANEL	Screen Size	65"
	Panel Technology	OLED
	Aspect Ratio	16 : 9
	Native Resolution	3,840 x 2,160
	Brightness	140/450 cd/m ² (APL* 100% / 25%) * Average Picture Level
	Contrast Ratio	140,000:1
	Color Gamut	129%
	Viewing Angle (H x V)	120 x 120
	Response Time	1ms (G to G) (Typ.), 8 ms (MPRT)
	Surface Treatment	Hard coating (2H), Anti-reflection
	Operation Hours	TBD
	Orientation	Portrait
CONNECTIVITY	Input	HDMI (HDCP 2.2, External)
	Output	-
	External Control	RS232C IN, RJ45, IR Receiver
PHYSICAL SPECIFICATION	Bezel Color	Black
	Bezel Width	15, 26, 13.2, 13.2 mm (U, B, L, R Off-bezel)
	Dimension (W x H x D)	(1 x 4 Model) Display: 3,123 x 2,120 x 8.54 mm (Module), 99 mm (Stand Neck)
	Weight	(1 x 4 Model) 380 kg
	Carton Dimensions (W x H x D)	1,038 x 858 x 1,281 mm (65EE5PC, include Pallet) 2,278 x 1,262 x 1,037 mm (65CVR4C, include Pallet)
	Packed Weight	TBD
	SPECIAL FEATURES	Temperature Sensor, Cooling FAN, Tile Mode, Source Selection (HDMI, DP), DPM Select, Energy Saving, Motion Eyecare, Internal Memory 128 GB (System 4 GB + Available 124 GB) Firmware update (LAN), HDMI-CEC, Fail over (DP, HDMI, Internal Memory) , DP daisy chain
ENVIRONMENT CONDITIONS	Operation Temperature	0°C to 40°C
	Operation Humidity	10% to 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
POWER CONSUMPTION	Typ.	230 W
	DPM	3 W
	Power Off	0.5 W
STANDARD (CERTIFICATION)	Safety	N/A
	EMC	FCC Class "A" / CE / KCC
	ErP / Energy Star	ErP
MEDIA PLAYER COMPATIBILITY	OPS Type Compatible	N/A
	External Media Player Attachable	N/A
SOFTWARE COMPATIBILITY	OLED SuperSign	Yes
	SuperSign C	Yes
ACCESSORY	Basic	Remote Controller (2ea batteries included), Power Cord, HDMI Cable, DP Cable 7ea, RS232C Cable 8ea, LAN Cable 9ea, QSG, Manual
	Optional	N/A
EAN		8806087863932