
EW5F-A | Scheda Tecnica

		55EW5F-A
PANEL	Screen Size	55"
	Panel Technology	OLED
	Aspect Ratio	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness (Typ.)	400/150 cd/m² (Average Picture Level 25%/100%, Panel)
	Transparency (Typ.)	38% (Panel)
	Viewing Angle (H x V)	178 x 178
	Response Time	1 ms (G to G), 8 ms (MPRT)
	Surface Treatment (Haze)	Hard Coating (2H), Anti-reflection Treatment of the Front Polarizer (Reflectance Typ. 14%)
	Life Time (Typ.)	30,000 Hrs
	Operation Hours	18 Hrs / 7 days *Moving Video Only
	Orientation	Landscape & Portrait
CONNECTIVITY	Input	HDMI, DP, USB (2)
	Output	DP, Audio
	External Control	RS232C In/out, RJ45 (LAN) In/out, IR In
MECHANICAL SPECIFICATION	Bezel Color	Silver
	Bezel Width	7.9 / 7.9 / 7.9 / 121.7 mm (T/B/L/R)
	Monitor Dimension (W x H x D)	(Head) 1,225.53 x 810.1 x 6.6 mm / (Signage Box) 782.8 x 238.4 x 34.7 mm
	Weight	(Panel and Glass Set) 12.3 kg / (Signage Box) 3.2 kg
	Carton Dimensions (W x H x D)	1,345 x 920 x 207 mm
	Packed Weight	22.4 kg
KEY FEATURE		Internal Memory (64GB), Temperature Sensor, Embedded CMS, Fail Over, Content Sync., OSD Rotation, Lock Mode, Content Rotation, Gapless Playback, Tile Mode Setting, Setting Data Cloning, Firmware Update by Network, SNMP, ISM Mode, \Control Manager, Crestron Connected*17, DPM, PM Mode, Wake on LAN, SI Server Setting, webRTC
ENVIRONMENT CONDITIONS	Operation Temperature	0°C to 40°C
	Operation Humidity	10% to 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
	Power Consumption Typ.	309 W *8 color bar
	Power Consumption Max.	318 W *8 color bar
CERTIFICATION	Safety	IEC 60950-1 / EN 60950-1 / UL 60950-1
	EMC	FCC Class "A" / CE / KC
	ErP / Energy Star	Yes / No
MEDIA PLAYER COMPATIBILITY	OPS Type Compatible	No
	External Media Player Attachable	Yes
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign CMS
	Control and Monitoring Software	SuperSign Control / Control+
ACCESSORIES	Basic	Remote Controller, Power Cord, QSG, IR Receiver, Regulation Book, Phone to RS232C Gender, RS232 Cable (4p-4p), FFC Cables (for Connection between Panel and Signage Box), DP Cable, LAN Cable, LC (VLC Cable), Tapes, Screws, Shield Cover Assy', Rubber Dampers

Connessioni

55EW5F-A

1. USB 2.0
2. HDMI IN
3. DP IN
4. DP OUT
5. USB 2.0
6. LAN IN
7. LAN OUT
8. IR IN
9. RS232C IN
10. RS232C OUT
11. AUDIO OUT



*I dati presenti in questa scheda tecnica sono soggetti a modifiche dovute ad aggiornamenti di prodotto. Vi invitiamo a consultare i manuali d'uso o il sito **www.lgbusiness.it** per verificare la congruità dei dati

EW5F-A | Disegno Tecnico

55EW5F-A

