

		65EV5E
PANEL	Screen Size	65"
	Panel Technology	OLED
	Aspect Ratio	16:9
	Native Resolution	3,840 x 2,160 (UHD)
	Brightness	400/150 cd/m2 (Average Picture Level 25%/100%)
	Color Gamut	-
	Viewing Angle (H x V)	178 x 178
	Operation Hours	12 Hrs / 7 Days *Moving Video Only
CONNECTIVITY	Orientation	Portrait
	Input	HDMI, DP, USB 2.0 (2)
	Output	HDMI, DP, USB 2.0 (2)
	External Control	RS232C In/out, RJ45 (LAN) In/out, IR In
PHYSICAL SPECIFICATION	Bezel Color	Black
	Bezel Width	1.2mm (Even) *Off-Bezel 9.1 mm (T/B), 8.7 mm (L), 11.6 mm (R) *On-Bezel 6.7 mm (Seam)
	Dimension (W x H x D)	1,634.6 x 1,446.7 x 7.9 mm (Head 1x2) 2,445.4 x 1,446.7 x 7.9 mm (Head 1x3) 782.8 x 35.5 x 239.0 mm (Signage Box)
	Weight	29.4 kg (Set 1x2) / 44.5 kg (Set 1x3)
	Carton Dimensions (W x H x D)	1,940 x 1,120 x 536 mm (Set 1x2) 1,940 x 1,120 x 646 mm (Set 1x3)
	Packed Weight	69.6 kg (Set 1x2, w/ Pallet) / 96 kg (Set 1x3, w/ Pallet)
	SPECIAL FEATURES	Internal Memory (64GB), Temperature Sensor, Embedded CMS (USB Auto Playback, Local Contents Scheduling, Group Manager), Fail Over, Content Sync (RS232C, Local Network), OSD Rotation, Lock Mode, Content Rotation, Gapless Playback, Tile Mode Setting, Setting Data Cloning, Firmware Update by Network, SNMP/ISM Mode, Control Manager, Crestron Connected1), DPM, PM Mode, Wake on LAN, Power on Delay, HDMI-CEC 2), SI Server Setting
ENVIRONMENT CONDITIONS	Operation Temperature	0°C ~40°C
	Operation Humidity	10% ~ 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Type	Built-In Power
POWER CONSUMPTION	Typ.	440 W *8 Color Bar Based
	DPM	-
	Power off	-
STANDARD (CERTIFICATION)	Safety	IEC 60950-1 / EN 60950-1 / UL 60950-1
	EMC	FCC Class "A" / CE / KC
	ErP/Energy Star	Yes / No
MEDIA PLAYER COMPATIBILITY	OPS-Type Compatible	No
	External Media Player Attachable	Yes
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign CMS
	Control and Monitoring Software	SuperSign Control+ / Control
ACCESSORIES	Basic (1x1)	Remote Controller, Power Cord, QSG, IR Receiver, Regulation Book, Phone to RS232C Gender, RS232 Cable (4p-4p), FFC Cables (for Connection Between Panel and Signage Box), DP Cable, LAN Cable, LC (VLC Cable), Fixer Screws, Anchor Bolts, Polyester Tapes, Panel Jigs
	Optional	-

1) Network Based Control 2) Compatibility may differ by equipment.

Connessioni

- 1

HDMI IN
- 2

DP IN
- 3

DP OUT
- 4

LAN IN
- 5

LAN OUT
- 6

RS232C IN

- 7

RS232C OUT
- 8

IR IN
- 9

AUDIO OUT
- 10

USB 2.0

