


		75TC3D	65TC3D	55TC3D
PANEL	Screen Size	75"	65"	55"
	Panel Technology	IPS	IPS	IPS
	Aspect Ratio	16 : 9	16 : 9	16 : 9
	Native Resolution	3,840 x 2,160 (UHD)	1,920 x 1,080 (FHD)	1,920 x 1,080 (FHD)
	Brightness*	500 cd/m ²	450 cd/m ²	450 cd/m ²
	Viewing Angle (H x V)	178 x 178	178 x 178	178 x 178
CONNECTIVITY	Input	HDMI (3), DP, DVI-D, RGB, Audio in, USB 3.0, USB 2.0, OPS USB 2.0		
	Output	Touch USB 2.0 (2)		
	External Control	RS232C in/out, RJ45 in		
PHYSICAL SPECIFICATION	Bezel Width	41.6 mm(T/L/R/B)	36.1mm(T/L/R), 42.2mm(B)	32.7mm (T), 33.4(L/R), 38.8 mm(B)
	Monitor Dimension (W x H x D)	1,732.8 x 1 011.1 x 69.7 mm (w/o Handle)	1,530.8 x 883.8 x 71.7 mm (w/o Handle)	1,276.4 x 751.9 x 63.9 mm
	Weight (Head)	74.5 kg	51 kg	29.1 kg
	Carton Dimensions (W x H x D)	1,870 x 1,264 x 285 mm (with pallet)	1,650 x 1,035 x 228 mm	1,369 x 890 x 210 mm
	Packed Weight	94 kg	59kg	34.9 kg
	VESA™ Standard Mount Interface	600 x 400 mm	300 x 300 mm	300 x 300 mm
KEY FEATURES	webOS 3.0+, IDB app, Crestron Connected® Certified, Mirroring, Soft AP, Beacon, Reader Mode, Auto Brightness Sensor, Internal Memory (64GB, System 8GB)			
SPECIAL FEATURES	Temperature Sensor, ISM method, DPM Select, Brightness Control, PM Mode, Wake on LAN, Energy Saving, File Play with USB, 2 PIP/PBP, Built-in Wi-Fi (802.11 n Combo), USB Cloning, Failover, No Signal Image			
ENVIRONMENT CONDITIONS	Operation Temperature Range	0°C to 40°C	0°C to 40°C	0°C to 40°C
	Operation Humidity Range	10% to 80%	10% to 80%	10% to 80%
POWER	Power Supply	100-240V~, 50/60Hz	100-240V~, 50/60Hz	100-240V~, 50/60Hz
	Power Type	Built-In Power	Built-In Power	Built-In Power
	Typ.	≤ 240 W	≤ 120 W	≤ 100 W
	Power Consumption Smart Energy Saving	≤ 170 W	≤ 85 W	≤ 70 W
	DPM	≤ 0.5 W	≤ 0.5 W	≤ 0.5 W
AUDIO	Built-in Speaker	20 W (10W×2)	20 W (10W×2)	20 W (10W×2)
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC	UL / cUL / CB / TUV / KC	UL / cUL / CB / TUV / KC
	EMC	FCC Class "A" / CE / KCC	FCC Class "A" / CE / KCC	FCC Class "A" / CE / KCC
MEDIA PLAYER COMPATIBILITY	OPS Type Compatible	Yes	Yes	Yes
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign Premium	SuperSign Premium	SuperSign Premium
	Control and Monitoring Software	SuperSign Link	SuperSign Link	SuperSign Link
ACCESSORY	Basic	Remote Controller (include battery 2ea), Power Cord, QSG, HDMI (3M), Regulation Book, Phone to RS232C Gender, Touch Pen (2ea), Eyebolt (2ea, 86TR3D only), Touch Pen Tip (1 ea, TC3D only)		
	Optional	OPS Kit (KT-OPSA), LSW640A/B (Wall Mount)		
TOUCH SPECIFICATIONS	Touch type	P-Cap(Ag Metal Mesh)	P-Cap(Ag Metal Mesh)	P-Cap(Ag Metal Mesh)
	Available object size for touch	more than Ø 6 mm	more than Ø 6 mm	more than Ø 6 mm
	Accuracy	2 mm	2 mm	2 mm
	Interface	USB 2.0	USB 2.0	USB 2.0
	Protection Glass Thickness	4T (Anti-Glare)	3.2T (Anti-Glare)	3.2T (Anti-Glare)
	Multi touch point	Max. 40 Points	Max. 40 Points	Max. 40 Points
EAN		TBD	TBD	TBD

Conessioni


75TC3D / 65TC3D / 55TC3D

- ① SPEAKER OUT
- ② RS-232C IN
- ③ RS-232C OUT
- ④ HDMI
- ⑤ EXT IR IN
- ⑥ AUDIO IN
- ⑦ AUDIO OUT
- ⑧ DVI-D IN
- ⑨ RGB IN
- ⑩ LAN
- ⑪ USB1
- ⑫ USB2

65/55TC3D REAR



75TC3D REAR



65/55/75TC3D SIDE

