

		55EG5CD	55EG5SD
PANEL	Screen Size	55"	
	Panel Technology	OLED	
	Aspect Ratio	16:9	
	Native Resolution	1,920 x 1,080 (FHD)	
	Brightness	100/400 cd/m ² (APL 100%/25%) *Average Picture Level	
	Viewing Angle (H x V)	178 x 178	
	Response Time	1 ms (G to G), 8 ms (MPRT)	
	Operation Hours	18 hrs/7 days (Moving video only)	
CONNECTIVITY	Orientation	Portrait	
	Input	HDMI (1+1), DP (1+1)	
	Output	DP (1+1), Audio, IR out (w/RS232C OUT Port Share)	
	External Control	RS232C in/out (1+1), RJ45 in/out (1+1), IR receiver (1+1), USB 3.0 (1+1)	
PHYSICAL SPECIFICATION	Bezel Color	Black	Black
	Bezel Width	(Off-bezel, with Glass) 101.3 / 81.3 / 81.3 / 81.3 mm (U/B/L/R) (On-bezel, with Glass) 107.9 / 87.9 / 88.5 / 91.6 mm (U/B/L/R) (On-bezel, w/o Glass, Only Panel) 6.6 / 6.6 / 7.2 / 10.3 mm (U/B/L/R)	(Off-bezel, with Glass) 101.3 / 81.3 / 81.3 / 81.3 mm (U/B/L/R) (On-bezel, with Glass) 107.9 / 87.9 / 91.6 / 88.5 mm (U/B/L/R) (On-bezel, w/o Glass, Only Panel) 6.6 / 6.6 / 10.3 / 7.2 mm (U/B/L/R)
	Dimension (W x H x D)	(Head) 861.3 x 1,406.2 x 13 mm (w/o Hanging Acc.) (T-Con Box) 312.2 x 213.4 x 16 mm (Signage Box) 412.6 x 222.4 x 64.3 mm	(Head) 872.7 x 2,050.9 x 500 mm (with Stand Accessory) (T-Con Box) 312.2 x 213.4 x 16 mm (Signage Box) 412.6 x 222.4 x 64.3 mm
	Weight	(Head) 31.2 kg (T-Con Box) 1.6 kg (Signage Box) 4.3 kg	(Head) 37 kg (TBD) (ACC-S-EG5D) 53 kg (TBD) (T-Con Box) 1.6 kg (Signage Box) 4.3kg
	Carton Dimensions (W x H x D)	1,880 x 1,015 x 363 mm	1,880 x 1,015 x 363 mm (Pallet: 1,800 x 363 x 120) 1,184 x 445 x 884 (ACC-S-EG5D)
	Packed Weight	71.4 kg (Glass Module 1 ea, T-Con Box 2ea, Signage Box 2ea)	78 kg (Glass Module 1ea, T-Con Box 2ea, Signage Box 2ea) TBD (ACC-S-EG5D)
	SPECIAL FEATURES	Temperature sensor, Cooling FAN, ISM method, DPM select, DPM wake up, Energy saving, Motion eye care, File play with USB, Internal memory (64 GB), USB cloning, Calibration mode, PM mode, Fail over, DP daisy chain	
ENVIRONMENT CONDITIONS	Operation Temperature	0°C to 40°C	
	Operation Humidity	10% to 80%	
POWER	Power Supply	100-240 V~, 50/60 Hz	
	Power Type	Built-in Power	
POWER CONSUMPTION	Typ.	190 W	
	DPM	3 W under	
	Power Off	0.5 W under	
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV / KC	
	EMC	FCC Class "A" / CE / KCC	
	ErP/Energy Star	Yes / NA	
MEDIA PLAYER COMPATIBILITY	OPS-Type Compatible	Yes	
	External Media Player Attachable	Yes	
SOFTWARE COMPATIBILITY	SuperSign OLED	Yes	
	SuperSign C	Yes	
ACCESSORIES	Basic	Remote controller (include battery 2ea), Power cord, QSG, HDMI cable (1m x 2ea for connection between T-Con box and signage box, 1.5m x 2ea), Power Hanness Cable (1m x 2ea for connection between T-Con box and signage box), IR receiver, Regulation book, Phone to RS232C gender, Jack cover, Signage box mounting bracket, T-Con box mounting bracket, FFC cable cover, Hanging Supporter front, Hanging supporter rear, Hanging supporter rear cover, FFC cable supporter assy, Ceiling bracket	Remote Controller (include battery 2ea), Power Cord, QSG, HDMI Cable (1m x 2ea for connection between T-Con box and signage box, 1.5m x 2ea), Power Hanness Cable (1m x 2ea for connection between T-Con box and signage box), IR receiver, Regulation Book, Phone to RS232C Gender (2 ea), Jack Cover, Signage Box Mounting Bracket, T-Con Box Mounting Bracket, FFC Cable Cover
	Optional	OPS kit (KT-OPSA)	OPS kit (KT-OPSA)
EAN		TBD	TBD