

		75
PANEL	Screen Size	75" (74.52" Measured Diagonal)
	Panel Technology	IPS, M+ (WRGB)
	Aspect Ratio	16 : 9
	Native Resolution	3,840 x 2,160 (UHD)
	Brightness	2,500 cd/m ² (Typ.), 2,250 cd/m ² (Min.)
	Contrast Ratio (Typ.)	1,200:1
	Viewing Angle (H x V)	178 x 178
	Surface Treatment	AGLR (Haze 3%), QWP
	Lifetime	50,000 Hrs
	Operation Hours	24 Hrs
	Orientation	Portrait (Clockwise) & Landscape
CONNECTIVITY	Input	HDMI(2), DP, DVI-D, Audio, USB 3.0, SD Card (FAT32/NTFS)
	Output	DP, External Speaker (L/R)
	External Control	RS232C In/out, RJ45 In, IR Receiver In
PHYSICAL SPECIFICATION	Bezel Color	Black
	Bezel Width	12.8 mm (Even)
	Monitor Dimension (W x H x D)	1,675.2 x 953.6 x 116 mm
	Weight (Head)	43 kg
	Carton Dimensions (W x H x D)	1,816 x 1,106 x 285 mm
	Packed Weight	52.2 kg
	VESA™ Standard Mount Interface	600 x 400 mm
SPECIAL FEATURES	Temperature Sensor, Auto Brightness Sensor (Except 75XS2C), Energy Saving, Smart Energy Saving, Tile Mode (Up to 15x15), Natural Mode@Tile Mode, Source Selection, Brightness/Contrast/Backlight, DPM Select, File Play with USB, Internal Memory (8GB, System 4GB + Available 4GB), Wi-Fi Dongle Ready	
ENVIRONMENTAL CONDITIONS	Operation Temperature	0°C to 40°C (w/o Direct Sunlight)
	Operation Humidity	10% to 85%
POWER	Power Type	Built-In Power
	Power Supply	100-240V~, 50/60Hz
	Power Consumption Typ. / Max.	585 W / 600 W
	Smart Energy Saving	280 W
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB / TUV
	EMC	FCC Class "A" / CE / KC / VCCI
	ErP / Energy Star	No / No
SOFTWARE COMPATIBILITY	Content Management Software	SuperSign CMS
	Control and Monitoring Software ¹	SuperSign Control
ACCESSORIES	Basic	Remote Controller (2 Batteries Included), Power Cord, HDMI Cable, Manual (ESG/EIG), IR Receiver (w/ Ambient Light Sensor)
	Optional	Wall Mount (LSW630), Wi-Fi Dongle (AN-WF500) *Stand is not available
EAN	8806087736267	

Conessioni

- 1 RS 232C IN
- 2 RS 232C OUT
- 3 SPEAKER OUT (8 Ω)
- 4 HDMI IN 1
- 5 HDMI IN 2
- 6 DP IN
- 7 DP OUT
- 8 DVI-D IN
- 9 SD CARD
- 10 USB IN
- 11 AUDIO IN (PC)
- 12 LAN
- 13 AC IN
- 14 IR & LIGHT SENSOR

