

		KT-T75E	KT-T65E	KT-T55E	KT-T49E	KT-T43E	KT-T32E
TOUCH	Touch Type	IR (Infrared Rays) Scattering	IR (Infrared Rays) Scattering	IR (Infrared Rays) Scattering	IR (Infrared Rays) Scattering	IR (Infrared Rays) Scattering	IR (Infrared Rays) Scattering
	Available Object Size for Touch	Φ6 mm↑ (Single), Φ8 mm↑ (Multi)	Φ6 mm↑ (Single), Φ8 mm↑ (Multi)	Φ6 mm↑ (Single), Φ8 mm↑ (Multi)	Φ6 mm↑ (Single), Φ8 mm↑ (Multi)	Φ6 mm↑ (Single), Φ8 mm↑ (Multi)	Φ6 mm↑ (Single), Φ8 mm↑ (Multi)
	Scan Time	15 ms ↓	15 ms ↓	15 ms ↓	15 ms ↓	15 ms ↓	15 ms ↓
	Accuracy	2 mm (Over 90% Area)	2 mm (Over 90% Area)	2 mm (Over 90% Area)	2 mm (Over 90% Area)	2 mm (Over 90% Area)	2 mm (Over 90% Area)
	Interface	USB 2.0	USB 2.0	USB 2.0	USB 2.0	USB 2.0	USB 2.0
	Protection Glass Thickness	3.2T (Anti-Glare)	2.8T (Anti-Glare)	2.8T (Anti-Glare)	2.8T (Anti-Glare)	2.8T (Anti-Glare)	2.8T (Anti-Glare)
	Protection Glass Transmission	85 ± 5%	85 ± 5%	85 ± 5%	85 ± 5%	85 ± 5%	85 ± 5%
	Operating System Support	Windows 7, Windows 8, Windows 8.1, Windows 10, Android (Kernel Version 3.5 Over), Linux (Kernel Version 3.5 Over), Mac OS X (10.9 Over), Chrome (39 or Above)					
	Multi Touch Point	Max 10 Points	Max 10 Points	Max 10 Points	Max 10 Points	Max 10 Points	Max 10 Points
	Screen Size	75"	65"	55"	49"	43"	32"
PANEL	Compatible Products	75UH5E, 75UM3E, 75UH5C, 75UM3C	65SM5(K)D, 65SE3(K)D	55SH7(P)E, 55SH7DD/E, 55SM5(K)D/E, 55SL5B/E, 55SL5PE, 55SM3C, 55SE3(K)D/DD/E	49SH7(P)E, 49SH7DD/E, 49SM5(K)D/E, 49SL5B/E, 49SL5PE, 49SM3C, 49SE3(K)D/DD/E	43SH7(P)E, 43SH7DD/E, 43SM5(K)D/E, 43SL5B/E, 43SL5PE, 43SM3C, 43SE3(K)D/DD/E	32SM5(K)D/E, 32SE3(K)D/E
	Brightness	N/A (Max 20% Brightness Reduction with Protection Glass)					
	Orientation	Landscape & Portrait	Landscape & Portrait	Landscape & Portrait	Landscape & Portrait	Landscape & Portrait	Landscape & Portrait
CONNECTIVITY	Input	USB	USB	USB	USB	USB	USB
PHYSICAL SPECIFICATION	Color	Black	Black	Black	Black	Black	Black
	Bezel Width	32.7 mm	32.7 mm	32.7 mm	32.7 mm	32.7 mm	32.7 mm
	Overlay Dimension (W × H × D)	1,722.1 × 1,000.3 × 29.3 mm	1,496.9 × 871.9 × 29.3 mm	1,278.0 × 748.8 × 29.3 mm	1,142.2 × 672.4 × 29.3 mm	1,009.6 × 597.8 × 29.3 mm	768.4 × 462.9 × 29.3 mm
	Weight (Head)	17 kg	12.9 kg	10.2 kg	7.8 kg	6.4 kg	4.2 kg
	Weight (Head w/ Dedicated Accessories)	18.9 kg	14.6 kg	11.1 kg	8.5 kg	7.1 kg	4.6 kg
	Carton Dimensions (W × H × D)	1,901.0 × 1,171.0 × 190.0 mm	1,676.0 × 1,042.0 × 190.0 mm	1,386.0 × 869.0 × 162.0 mm	1,250.0 × 792.0 × 162.0 mm	1,170.0 × 710.0 × 152.0 mm	866.0 × 575.0 × 152.0 mm
	Packed Weight	27.2 kg	21.3 kg	13.5 kg	12.7 kg	9.9 kg	7 kg
SPECIAL FEATURES	Language (Manual)	English, Spanish, Korean, French	English, Spanish, Korean, French	English, Spanish, Korean, French	English, Spanish, Korean, French	English, Spanish, Korean, French	English, Spanish, Korean, French
ENVIRONMENT CONDITIONS	Operation Temperature	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C	0°C to 40°C
	Operation Humidity	10% to 80%	10% to 80%	10% to 80%	10% to 80%	10% to 80%	10% to 80%
POWER	Power Supply	USB	USB	USB	USB	USB	USB
	Max.	1.8 W	1.8 W	1.8 W	1.8 W	1.8 W	1.8 W
ACCESSORIES		Overlay Manual (CD), Pen (2), Pen Tray, Install Accessories	Overlay Manual (CD), Pen (2), Pen Tray, Install Accessories	Overlay Manual (CD), Install Accessories	Overlay Manual (CD), Install Accessories	Overlay Manual (CD), Install Accessories	Overlay Manual (CD), Install Accessories