

		49WEC-CB
PANEL	Screen Size	49"
	Panel Technology	IPS (M+)
	Transmittance	9.50%
	Aspect Ratio	16:9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	100 cd/m ² (Typ), 80 cd/m ² (Min) / (Integrated with protection glass + white reflector sheet (TXD-225))
	Color Depth	16.7 Million
	Response Time (Typ)	9 ms (G to G BW)
	Orientation	Portrait
CONNECTIVITY	Input	-
	Output	-
	External Control	IR Receiver, USB
PHYSICAL SPECIFICATION	Bezel Color	Silver
	Bezel Width	184.6 mm (T), 223.6 mm (D), 60 mm (L/R)
	Cooler Dimension	730 x 773 x 1,861 mm
	Net Weight	114 kg
	Carton Dimensions	765 x 801 x 2,037.5 mm
	Packed Weight	162 kg
	Handle	Yes
SPECIAL FEATURES		Temperature Sensor, File Play with USB, Internal Memory 8 GB (System 4 GB + Available 4 GB), Wi-Fi (In-Box), USB Cloning
ENVIRONMENT CONDITIONS	Operation Temperature	5°C to 35°C
	Operation Humidity	10% - 80%
POWER	Power Supply	220-240V~ 50Hz 2.5 A
	Power Type	Adaptor (Built-in)
	Power Consumption (Typ./Max)	300Wh (Typ), 450Wh (Max) - Test Condition: Normal Temperature (25+/- 2°C) : Keep the door closed condition. Do not allowed door open/close.
STANDARD (CERTIFICATION)	Safety	CE
	EMC	CE
	ErP / Energy Star	N/A
SOFTWARE COMPATIBILITY	SuperSign W/UTE	Yes
	SuperSign C	Yes
ACCESSORIES	Basic	Remote Controller (including battery 2ea), WiFi Dongle, Anker Bolt (1 set), Rubber Pad (12ea)
	Optional	X
TRANSPARENT COOLER	Protection Glass	3.2T Tempered Glass
	Hybrid Display	Hybrid / Semi-Transparent
	Brightness Control	Yes
	Compatible Cooler Body	Premier FRS-500R
	Sensor	Proximity Sensor (Lower-center door), Door sensor
COOLER BODY	Volume	479 L
	Temperature Adjust	0°C - 10.0°C (32°F - 50°F)
	Compressor Power	1/4 HP
	Shelves	4
	Foaming Agent	Cyclopentane
	Safety / EMC	CE / CE (Class B)
	Manufacturer	TurboAir Korea
	Power Input	220-240V~ 50 Hz
	RoHS	RoHS, REACH
	Refrigent. Type	R-134a
	Charge	0.220 kg
	GWP	1,430 (kgCO ₂ -eq)
	CO ₂ -Equivalent	0.315 (Ton)
	Door Lock	None
EAN		8806087573992

49WEC
730 x 773 x 1,861 /
114 kg

